



LABORATÓRIO NACIONAL
DE ENGENHARIA CIVIL

MARSol Workshop: Monitoring and Investigation Technologies, March 16th-17th 2015, Athens

DEMO SITE 2: ALGARVE AND ALENTEJO, SOUTH PORTUGAL


Teresa Leitão (LNEC)
João Paulo Lobo Ferreira (LNEC)
Manuel Oliveira (LNEC)
Tiago Carvalho (TARH)
Rita Carvalho (TARH)
Raquel Sousa (TARH)
Rui Agostinho (TARH)
José Paulo Monteiro (UAlg)
Luís Costa (UAlg)

DEMO Site 2: Algarve and Alentejo, South Portugal



PT1 Algarve, Rio Seco


- Recharge goal: Improvement of water quality in a nitrate vulnerable zone;
- Recharge concept: Infiltration basins in river bed and infiltration dug wells “Noras”;
- Monitoring concept:
 - 4 “short” piezometers in the basins (manual measurements)
 - 4 piezometers in the upper aquifer unit (Upper Miocene) next to the basins
 - 1 piezometer located upstream of the basins (control)
 - 1 water well (not in operation) for monitoring the lower aquifer subunit (Lower Miocene)
 - Dug wells scattered across territory for Water quality



LABORATÓRIO NACIONAL
DE ENGENHARIA CIVIL




DEMO Site 2: Algarve and Alentejo, South Portugal



DEMO Site 2: Algarve and Alentejo, South Portugal




DEMO Site 2: Algarve and Alentejo, South Portugal



DEMO Site 2: Algarve and Alentejo, South Portugal

PT1 Algarve, rio Seco

- Infiltration tests (Set/Out 2014 and Jun 2015)
- Tracer tests with NaCl (Out 2014)
- Continuous monitoring of infiltration basins (on-going)



Saturated zone monitoring equipment



Groundwater sampling and *in situ* measurement equipment

CTD-Diver



- Robust, durable, corrosion proof housing
- Conductivity range 0 to 120 mS/cm

[Request Pricing »](#)

Corrosion Proof Multi-parameter Groundwater Datalogger

Features

- Innovative ceramic housing technology
- Three sensors in one sealed housing
- Conductivity range up to 120 mS/cm
- Compact size: Ø 22 mm - length 135 mm
- Various measurement methods
- 48,000 records of time stamp, pressure, temperature and conductivity
- 30-Point pressure factory calibration





LABORATÓRIO NACIONAL
DE ENGENHARIA CIVIL






DEMO Site 2: Algarve and Alentejo, South Portugal

- Yearly monitoring campaign (May)
- Manual sampling (bailer)
- UV-Molecular Absorption spectrometry







Nitrate concentration in the groundwater of Campina de Faro aquifer (PT1_3 Campina de Faro) in April 2008 and May 2014

DEMO Site 2: Algarve and Alentejo, South Portugal




DEMO Site 2: Algarve and Alentejo, South Portugal



DEMO Site 2: Algarve and Alentejo, South Portugal

PT1_2 Algarve, MARSol basins:

- Continuous monitoring of natural infiltration (on-going)




Source: LNEC


DEMO Site 2: Algarve and Alentejo, South Portugal

PT1_3 Algarve, large-diameter wells:

- Infiltration test, 3 flowrates (Sept 2014)



Infiltration capacity
 $> 34 \text{ m}^3/\text{h}!$




Source: UAlg


DEMO Site 2: Algarve and Alentejo, South Portugal

PT2_6 Algarve, Cerro do Bardo


- Recharge goal: Improve availability of groundwater resources in a high yield karst aquifer, using winter surface water surplus;
- Recharge concept: Infiltration in a dug well and natural sinkholes
- Monitoring concept:
 - 1 Dug well
 - 2 Piezometers
 - Private water wells



DEMO Site 2: Algarve and Alentejo, South Portugal





DEMO Site 2: Algarve and Alentejo, South Portugal



DEMO Site 2: Algarve and Alentejo, South Portugal

PT2_6 Algarve, Cerro do Bardo


- Infiltration test in the large well (April 2014).
- Infiltration test with tracer (NaCL) with geophysics support (Dec 2014).
- Pumping test in CB2 in February 2016
- Infiltration rates (in the well): above 20 m³/h.
- Local hydraulic conductivities between 0,08 to 0,20 m/d.



DEMO Site 2: Algarve and Alentejo, South Portugal

PT2_6 Algarve, Cerro do Bardo

- Geophysical Monitoring




Source: LNEC




LABORATÓRIO NACIONAL
DE ENGENHARIA CIVIL



DEMO Site 2: Algarve and Alentejo, South Portugal



DEMO Site 2: Algarve and Alentejo, South Portugal



LABORATÓRIO NACIONAL
DE ENGENHARIA CIVIL




Date (dd/mm/yy)




- **PT2_4 Algarve, São Bartolomeu de Messines**
- Recharge goal: Improve WWTP effluent that is currently discharged to a river crossing a high yield karst aquifer
- Recharge concept: Infiltration and drainage in two SAT basins
- Monitoring concept:
 - 3 flowmeters;
 - Manual outflow sampling
 - Teflon cups at 2 different depths in the vadose zone
 - Monitoring of pH, TSS, COD, BOD5, N total, P total, N-NH4, N-NO3, faecal coli, EC, all N forms, phosphates and sulphates (Águas do Algarve)
 - Monitoring of persistent pollutants (LNEC)

DEMO Site 2: Algarve and Alentejo, South Portugal



Vadose zone monitoring equipment



Conclusions:

- All constructed monitoring structures are operational and working properly;
- Monitoring results were fundamental for the calibration of the hydrogeological conceptual model;
- The presence of a control well (out of the MAR influence area) is fundamental to access the role of natural and managed recharge;
- PT_4: S. Bartolomeu de Messines WTPP monitoring network will be implemented soon after basins installation;
- Vadose Zone:
 - Campina de Faro: Permeable just in the basins,
 - Cerro do Bardo: Hard to monitor (karstified structures)
 - S.Bartolomeu de Messines WWTP SAT basins: No direct connection to aquifer
- Aquifer monitoring: What is the recharge effect range?
- Inventory: make an exhaustive search. Know what you have...